HET949BSC



Induction hob with hood







₪) Noise level

1 ChildLock

EasyClean

PowerBoost

MinimalDesign

TouchControl

Flush installation

Extraction or recirculation

Clean indicators

Hood timer

Hob timer

*

SoftMelt

Electronic control

Control setting: Touch control

Timer function

Number of speed positions: 9

Overheat protection

Power boost

AreaFlex

Flush installation

SoftMelt

Venting with air extraction or recirculation

4 induction heating zones Left front: Ø 21×19 cm, 2.1/3 kW, Right front: Ø 21×19 cm, 2.1/3 kW, Left rear: Ø 21×19 cm, 2.1/3 kW, Right rear: Ø

Energy class: A++

Grease filtering efficiency class: **B** Fluid dynamic efficiency class: **A**

Maximum extraction rate by extraction operation: 620 m³/h
Maximum extraction rate by recirculation operation: 332 m³/h

Air flow by extraction version, step 2: **414** m³/h
Air flow by extraction version, step 3: **620** m³/h

Airflow boost position (PowerBoost 1) - extraction: 700 m³/h

Number of PowerBoost functions: 1
Number of power levels: 9

Number of motors: 1

ChildLock

Grease filter indicator

Filter material: **Aluminium**Washable grease filter

Max. noise level: **66 dB(A)re 1 pW**Annual energy consumption: **29 kWh**Dimensions (W×H×D): **83 × 23 × 52 cm**

Dimensions of packed product (W×H×D): 102 × 48 × 76 cm

Niche dimensions (WxHxD): 77 x 24 x 49 cm

Net weight: 19 kg Gross weight: 26 kg Connected load: 7,620 W Product code: 738958 EAN code: 3838782530951

